BADGER ORDNANCE BOLT KNOB INSTALLATION FORM

Thank you for choosing Badger Ordnance for your Remington 700 bolt upgrade. All work is performed at our service center and carries carries an approx. turn around time of 10 business days once in house. Upon completion, your bolt will be returned via UPS Ground shipment and insured for a value of \$400. Listed below are a few requirements that will ensure prompt processing and return of your completed bolt. **WE WILL NOT INSTALL OTHER COMPANIES KNOBS.**

- 1. Badger Ordnance Bolt Knob installation can only be performed on Remington 700 bolts. Please ensure that the bolt you intend to upgrade is for a Remington 700.
- 2. All orders are processed via UPS Ground shipment, and therefore require a physical street address for delivery. UPS WILL NOT ship to PO Box addresses.
- 3. Be sure to include ALL payment information on this form. We can not call for payment information. Orders without credit number included will not be processed.
- 4. Allow 15 days from the time you ship your bolt before checking on the status. Please use tracking information to determine if your bolt has arrived at our location.

SHIPPING INFORM	ATION						
ADDRESS		APT/SUITE					
CITY		_STATE	ZIP	_E-mail			
For tracking go to	www.ups.com/myd	choice and sigi	n up, this will allow	you to track you	ur order and even sch	nedule delivery times.	
No, I have not in Add \$18.00 for If you need a Bolt K BLACK TAN OD GREEN PAYMENT TYPE	uded a previously puro ncluded a Badger Bolt shipping to Alaska and (nob provided, please s BRIGHT GREEN BRIGHT RED BRIGHT BLUE	Knob and will not Hawaii. pecify color: MINI KNOI	eed one supplied for B, Black only (add \$2.	installation at a tota	Send to: Badger Ordr 401 Blackha	nance / RBGC wk St	
Personal check, amount sent \$ Money Order, amount sent \$					Weston, MO. 64098 816 386 4021		
Credit Card,	amount authorized \$_			ster card	010 000 402	.,	
CC NUMBER	/	//	/	EXP	CVN	- 200	420
5	Parallel	Parallel Parallel	B	, s	C	D	
•••	IIS KNOB IS FOR INSTA						
Warning: This Bolt knob must be installed by a competent gunsmith. Making sure that the firearm is unloaded, Remove the bolt from the rifle and disassemble the firing pin assembly.							
 Place the bolt in a machine vise with the back of the handle parallel to the axis of the machines head. (fig. A) Using a hollow mill or a boring head, turn the existing bolt knob down to a boss .313" dia. (fig. B) Then mill the end of the boss off leaving a straight section .6" long. Thread the entire straight section 5/16-24 NF. (fig. C) 					Regular Knob	r Mini Knob	
 Degrease the threads and test the fit of the knob, (fig. D) If the knob fits correctly, 						Made in the USA	
5. When the thread	cker to the threads, we s locker has cured, re-ass scope of your equipmer	semble the bolt an	t and install into the rifle.		Unless otherwise specified Diminsions are in Inches TOLERANCES: ANGLES ± .5°	BADGER ORDNAND 816 421-4956 FAX 816 421	
	See installation instruction				FRACTIONS ±.015 .0001 .000005	Tactical Bolt Knob	_
					.00000005	Dwg No. 306-31-2 Part No. 306-31	

ENGINEER: M. BORDSON

Scale NONE Date: 20 Apr 2020 Page